

Project Name \_\_\_\_\_

Fixture Type \_\_\_\_\_



ENERGY  
SAVING



LOW  
MAINTENANCE



ENVIRONMENTALLY  
FRIENDLY



RETAIL




COMMERCIAL

### Features:


- Designed for CFL PLC lamp replacement
- High efficiency LEDs
- Isolated LED Driver with PF>0.95
- Easy installation
- Fully compatible with existing 6" & 8" downlight fixture
- Long lifespan >30,000h
- Powerful light output and efficient heat dissipation
- 270° rotatable with a 140° beam angle
- No UV and IR Radiation
- 3 Year Warranty

### Schematics & Installation

Remove the ballast and connect the mains to the lamp socket



Lamp Socket



Rotation Angle 270°

### Specifications:

MODEL	ORR-PLC1-5-E26	ORR-PLC2-7-E26	ORR-PLC3-7-GX23
Designed to replace	13W CFL - 6" Downlight	18W CFL - 8" Downlight	18W CFL - 8" Downlight
Rated lamp life	30 000 h	30 000 h	30 000 h
Rated voltage	85-265V	85-265V	85-265V
Energy consumption	5W	7W	7W
Luminous Flux	430lm	595lm	690lm
CRI	+70	+70	+70
Dimmable	No	No	No
Beam Angle	140°	140°	140°
CCT	3000K, 4000K	3000K, 4000K	3000K, 4000K

